



FEATURES:



- 5 μ m resolution
- IP degree: IP 65
- $\pm 20\mu$ m accuracy
- Full symmetrical
- LED status indicators
- Adjustable reference
- Measuring range from 150mm to 2000mm
- Protective steel cover for measurement tape
- High precision bearings for smooth movement

→ The Magnetic Linear Encoder is supplied with
PRECISION MECHANICAL SCREW

TRIVENETA IMPIANTI S.r.l.

Administrative Headquarters: Via Scopella, 22 - 37060 Castel d'Azzano VR - Italy

Operational Headquarters: Via Bovolino, 18/B - 37060 Buttapietra VR - Italy

Phone: +39 045 518 747 - Fax +39 045 854 56 05 - Web Site: www.trivenetaimpianti.com E-mail: sales@trivenetaimpianti.com

MODEL SPECIFICATIONS

Pole pitch: 5mm





Measurement stroke: 400mm

Adjustable reference


Resolution: 5 μ m

Output Type: TTL Linedriver

Supply Voltage: 5V DC



PIN CONFIGURATION



Cable output

V+ : Brown
0V : Blue
A : Black
B : White
Z : Orange
A inv. : Yellow
B inv. : Green
Z inv. : Red
GND : Earth

9G Type Electrical Connection

Pin 1 : Ch A
Pin 2 : Ch A inv.
Pin 3 : Ch Z
Pin 4 : Ch B
Pin 5 : Ch B inv.
Pin 6 : Ch Z inv.
Pin 7 : +V
Pin 8 : GND
Pin 9 : Earth

9H Type Electrical Connection

Pin 1 : Ch Z
Pin 2 : Ch B
Pin 3 : Ch A
Pin 4 : NC
Pin 5 : GND
Pin 6 : Ch Z inv.
Pin 7 : Ch B inv.
Pin 8 : Ch A inv.
Pin 9 : +V

TRIVENETA IMPIANTI S.r.l.

Administrative Headquarters: Via Scopella, 22 - 37060 Castel d'Azzano VR - Italy

Operational Headquarters: Via Bovolino, 18/B - 37060 Buttapietra VR - Italy

Phone: +39 045 518 747 - Fax +39 045 854 56 05 - Web Site: www.trivenetaimpianti.com E-mail: sales@trivenetaimpianti.com